

ANNEXURE III - S

SPECIFICATION DETAILS OF DIRECT BULK PACK

PRODUCT: Mangoes - Alphonso

CAPACITY: 12 nos.

MATERIAL OF CONSTRUCTION *	Corrugated Fibre	Corrugated Fibre	Corrugated Fibre	Corrugated Fibre
	Board	Board	Board	Board
EXTERNAL DIMENSIONS (mm)	320 x 230 x 90	320 x 230 x 90	320 x 230 x 90	320 x 230 x 90
STYLE OF BOX * *	RSC - 0201	Telescopic - 0300	Telescopic - 0306	Telescopic - 031
NO. OF PLIES	5.0	Lid - 3 Tray - 3	Lid - 3 Tray - 3	Lid - 3 Tray - 5
TYPE OF FLUTES	B /B (Narrow)	Lid B (Narrow) Tray B (Narrow)	Lid B (Narrow) Tray B (Narrow)	Lid B (Narrow) Tray B / B(Narrov
DIRECTION OF FLUTES	Vertical	Vertical	Vertical	Vertical
GRAMMAGE (G/M SQ.) OUTER TO INNER (INDICATIVE)	250 / 120 / 120 / 120 / 120	Lid : 250/150/150 Tray : 250/150/150	Lid : 250/150/150 Tray : 250/150/150	Lid: 250/150/15 Tray: 250/120/12 120 / 120
BURST FACTOR OF PAPER (KRAFT) (MINIMUM)	20.0	20.0	20.0	20.0
BURSTING STRENGTH OF BOARD (KG/CM.SQ)(MINIMUM)	14.0	Lid : 11.0 Tray : 11.0	Lid : 11.0 Tray : 11.0	Lid : 11.0 Tray : 11.0
NO. OF PIECES PER BOX	Not more than two	Not more than two	Not more than two	Not more than to
MANUFACTURE'S JOINT	By gluing	By gluing	By gluing	By gluing
EDGE CRUSH (KGF) (MIN)	39.00	39.00	39.00	39.00
COMPRESSION STRENGTH OF BOX (KGF) (MINIMUM)	450	450	450	450
COBB (30 MINUTES) *** (G/M SQ.) (MAXIMUM)	60	60	60	60
NO. OF VENTILATION HOLES	16.0	16.0	16.0	16.0
DIAMETER (MM) OF POSITION OF HOLES	20.0	20.0	20.0	20.0
TWO SIDES EACH TWO ENDS EACH TOP & BOTTOM EACH	3 1 4	3 1 4	3 1 4	1 4

Outer ply of white duplex board or bleached kraft

Note: Dimensions of the box are modular to Euro pallets. However, any other dimensions or box styles to suit importers requirements could also be used.

Or any other suitable style which provides equal strength and performance

Outer ply to be laminated or coated for water proofing